



# JL-M Lubricant

## Safety Data Sheet

according to ANSI Z400.1

Date of issue: 03/04/2013

Revision date: 03/04/2013

Supersedes date: 04/06/2009

Version 1.0

### SECTION 1. Product and company identification

Chemical type : Mixture  
Trade name : JL-M Lubricant  
Company identification : Superbolt, Inc.  
1000 Gregg Street  
Carnegie, PA 15106  
T (412) 279-1149  
www.nord-lock.com/  
Emergency number : (412) 279-1149 (Monday- Friday from 7:30 am – 4:30 pm; North American Eastern Time Zone)

### SECTION: 2. Hazards identification

#### 2.1. Emergency Overview

Physical state : Solid  
Appearance : Paste  
Colour : Dark grey  
Odour : Mild petroleum odor

HAZARD : May cause cancer

Quartz(14808-60-7)	
IARC group	1 - Carcinogenic to Humans
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens
	In OSHA Hazard Communication Carcinogen list

#### 2.2. OSHA Regulatory Status

OSHA regulation Status : This material is classified as hazardous under OSHA regulation

#### 2.3. Potential health effects

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.  
Symptoms/injuries after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.  
Symptoms/injuries after skin contact : May cause skin irritation.  
Symptoms/injuries after eye contact : Symptoms include : Redness. Blurred vision.  
Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

#### 2.4. Potential environmental effects

No additional information available

### SECTION: 3. Composition/information on ingredients

Name	CAS No.	%
Molybdenum Disulfide	1317-33-5	< 60
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	< 35
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	
Graphite	7782-42-5	< 15
Quartz	14808-60-7	< 0.5

### SECTION: 4. First aid measures

#### 4.1. First aid procedures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).  
First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.  
First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation persists, seek medical attention.  
First-aid measures after eye contact : Rinse immediately with plenty of water, also under the eyelids. Obtain medical attention if pain, blinking or redness persist.  
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Obtain emergency medical attention.

#### 4.2. Note to physicians

Treat symptomatically.



# JL-M Lubricant

## Safety Data Sheet

according to ANSI Z400.1

### SECTION: 5. Firefighting measures

#### 5.1. Flammable properties

- Fire hazard : Decomposition products may be a hazard to health.  
Explosion hazard : Exposure to fire may cause containers to rupture/explode.  
Reactivity : Stable under normal conditions of use.

#### 5.2. Extinguishing media

- Suitable extinguishing media: : Foam. Dry powder. Carbon dioxide. Water spray. Sand.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.3. Protection for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.  
Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION: 6. Accidental release measures

#### 6.1. Personal precautions

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable protective clothing gloves, and eye/face protection.  
Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Wear suitable protective clothing, gloves and eye/face protection.  
Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods for containment

No additional information available

#### 6.4. Methods for clean up

- Methods for cleaning up : Clean spills promptly. Wear proper protective equipment. Dispose in a safe manner in accordance with local/national regulations.

#### 6.5. Other information

See Heading 8. Exposure controls and personal protection.

#### 6.6. Spill or leak statements by type of chemical

No additional information available

### SECTION: 7. Handling and storage

#### 7.1. Handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapour.  
Hygiene measures : Handle in accordance with good industrial hygiene and safety practices. Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

#### 7.2. Storage

- Storage condition(s) : Keep only in the original container in a cool, well ventilated place away from : open sparks and flame. Keep container closed when not in use.  
Incompatible products : Strong oxidizing agents.  
Incompatible materials : Sources of ignition. Direct sunlight.

### SECTION: 8. Exposure controls/personal protection

#### 8.1. Exposure guidelines

Molybdenum Disulfide (1317-33-5)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable fraction)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (insoluble compounds, total dust)
Québec	VECD (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (insoluble compounds)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Québec	VECD (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral oil - dust)



# JL-M Lubricant

## Safety Data Sheet

according to ANSI Z400.1

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
Québec	VEMP (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral oil - dust)
Graphite (7782-42-5)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup> (respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (respirable fraction)
Québec	VECD (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (respirable dust)
Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup>
IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Québec	VEMP (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>

### 8.2. Engineering controls

Appropriate engineering controls : Ensure adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Personal protective equipment (PPE)

Personal protective equipment : Protective goggles. Gloves.



Hand protection : Wear protective gloves.  
Eye protection : Chemical goggles or safety glasses.  
Respiratory protection : An approved organic vapour respirator/supplied air or self-contained breathing apparatus must be used when vapour concentration exceeds applicable exposure limits.

## SECTION: 9. Physical and chemical properties

Physical state : Solid  
Appearance : Paste.  
Colour : Dark grey.  
odour : Mild petroleum odor.  
Odour threshold : No data available  
pH : Not applicable  
Melting point : No data available  
Freezing point : No data available  
Boiling point : > 315 °C (600°F)  
Flash point : 190 °C (374°F)  
Relative evaporation rate (butylacetate=1) : No data available  
Flammability (solid, gas) : No data available  
Explosive limits : No data available  
Vapour pressure : < 0.1 mm Hg  
Relative vapour density at 20 °C : > 2 (Air = 1)  
Relative density : 4.8  
Solubility : Water: Negligible in water  
Log Pow : No data available  
Self ignition temperature : No data available  
Decomposition temperature : No data available  
Viscosity : No data available  
Explosive properties : Not explosive.  
Oxidising properties : Not oxidizing.

No additional information available

## SECTION: 10. Stability and reactivity

### 10.1. Chemical stability

Stable under normal conditions of use.



# JL-M Lubricant

## Safety Data Sheet

according to ANSI Z400.1

### 10.2. Conditions to avoid

Heat, open flame, sparks, hot surfaces, ignition sources, elevated temperature.

### 10.3. Incompatible materials

Strong oxidizing agents.

### 10.4. Hazardous decomposition products

On combustion, forms: fume. Carbon monoxide. Carbon dioxide. Sulfur oxides. Aldehydes. Nitrogen oxides (NO<sub>x</sub>).

### 10.5. Possibility of hazardous reactions

Product will not undergo polymerization.

## SECTION: 11. Toxicological information

### Information on toxicological effects

Acute toxicity : Not classified  
Based on available data, the classification criteria are not met

Molybdenum Disulfide (1317-33-5)	
LC50 inhalation rat (mg/l)	> 2820 mg/m <sup>3</sup> (Exposure time: 4 h)
Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 4.7 mg/l (Exposure time: 4 h)
Quartz (14808-60-7)	
LD50 oral rat	500 mg/kg

Skin corrosion/irritation : Not classified  
Based on available data, the classification criteria are not met

Serious eye damage/irritation : Not classified  
Based on available data, the classification criteria are not met

Respiratory or skin sensitisation : Not classified  
Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified  
Based on available data, the classification criteria are not met

Carcinogenicity : May cause cancer

Reproductive toxicity : Not classified  
Based on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) : Not classified  
Based on available data, the classification criteria are not met

Specific target organ toxicity (repeated exposure) : Not classified  
Based on available data, the classification criteria are not met

Aspiration hazard : Not classified  
Based on available data, the classification criteria are not met

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

## SECTION: 12. Ecological information

### 12.1 Ecotoxicity

Petroleum distillates, hydrotreated heavy paraffinic(64742-54-7)	
LC50 fish	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Distillates, petroleum, solvent-dewaxed heavy paraffinic(64742-65-0)	
LC50 fish	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and degradability

JL-M Lubricant	
Persistence and degradability	Not established.

### 12.3. Bioaccumulation/Accumulation

JL-M Lubricant	
Bioaccumulative potential	Not established.



# JL-M Lubricant

## Safety Data Sheet

according to ANSI Z400.1

### 12.4. Mobility in environmental media

No additional information available

### 12.6. Other adverse effects

Other information : Avoid release to the environment.

## SECTION: 13. Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

## SECTION: 14. Transport information

### 14.1. Basic shipping description

No additional information available

### 14.2. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

## SECTION: 15. Regulatory information

### 15.1. US Federal regulations

#### Molybdenum Disulfide (1317-33-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Petroleum distillates, hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Graphite (7782-42-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### Molybdenum Disulfide (1317-33-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification

Uncontrolled product according to WHMIS classification criteria

#### Petroleum distillates, hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Graphite (7782-42-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

#### Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

#### EU-Regulations

#### Molybdenum Disulfide (1317-33-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.



# JL-M Lubricant

## Safety Data Sheet

according to ANSI Z400.1

### Petroleum distillates, hydrotreated heavy paraffinic (64742-54-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

### Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

### Graphite (7782-42-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

### Quartz (14808-60-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

### 15.2.2. National regulations

#### Molybdenum Disulfide (1317-33-5)

Listed on the AICS (the Australian Inventory of Chemical Substances).  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Pollutant Release and Transfer Register Law (PRTR Law)

#### Petroleum distillates, hydrotreated heavy paraffinic (64742-54-7)

Listed on the AICS (the Australian Inventory of Chemical Substances).  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)

#### Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

Listed on the AICS (the Australian Inventory of Chemical Substances).  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)

#### Graphite (7782-42-5)

Listed on the AICS (the Australian Inventory of Chemical Substances).  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)

#### Quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)  
Listed on the AICS (the Australian Inventory of Chemical Substances).  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed as carcinogen on NTP (National Toxicology Program)

### 15.3. US State regulations

#### Molybdenum Disulfide (1317-33-5)

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
----------------------------	--

#### Petroleum distillates, hydrotreated heavy paraffinic(64742-54-7)

State or local regulations	U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
----------------------------	---

#### Distillates, petroleum, solvent-dewaxed heavy paraffinic(64742-65-0)

State or local regulations	U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
----------------------------	---



# JL-M Lubricant

## Safety Data Sheet

according to ANSI Z400.1

Graphite(7782-42-5)	
State or local regulations	<p>U.S. - Hawaii - Occupational Exposure Limits - TWAs                      U.S. - Idaho - Occupational Exposure Limits - Mineral Dusts                      U.S. - Idaho - Occupational Exposure Limits - TWAs                      U.S. - Massachusetts - Right To Know List                      U.S. - Michigan - Occupational Exposure Limits - TWAs                      U.S. - Minnesota - Hazardous Substance List                      U.S. - Minnesota - Permissible Exposure Limits - TWAs                      U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour                      U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual                      U.S. - New Jersey - Right to Know Hazardous Substance List                      U.S. - New York - Occupational Exposure Limits - Mineral Dusts                      U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour                      U.S. - Oregon - Permissible Exposure Limits - Mineral Dusts                      U.S. - Oregon - Permissible Exposure Limits - TWAs                      U.S. - Pennsylvania - RTK (Right to Know) List                      U.S. - Tennessee - Occupational Exposure Limits - TWAs                      U.S. - Texas - Effects Screening Levels - Long Term                      U.S. - Texas - Effects Screening Levels - Short Term                      U.S. - Vermont - Permissible Exposure Limits - TWAs                      U.S. - Washington - Permissible Exposure Limits - STELs                      U.S. - Washington - Permissible Exposure Limits - TWAs                      U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet                      U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet                      U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater                      U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet</p>

Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	Yes
<p>U.S. - Hawaii - Occupational Exposure Limits - TWAs                      U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations                      U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)                      U.S. - Idaho - Occupational Exposure Limits - Mineral Dusts                      U.S. - Illinois - Toxic Air Contaminant Carcinogens                      U.S. - Maine - Chemicals of High Concern                      U.S. - Massachusetts - Right To Know List                      U.S. - Michigan - Occupational Exposure Limits - TWAs                      U.S. - Minnesota - Chemicals of High Concern                      U.S. - Minnesota - Hazardous Substance List                      U.S. - Minnesota - Permissible Exposure Limits - TWAs                      U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour                      U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual                      U.S. - New Jersey - Right to Know Hazardous Substance List                      U.S. - New Jersey - Special Health Hazards Substances List                      U.S. - Oregon - Permissible Exposure Limits - Mineral Dusts                      U.S. - Pennsylvania - RTK (Right to Know) List                      U.S. - Rhode Island - Hazardous Substance List                      U.S. - Tennessee - Occupational Exposure Limits - TWAs                      U.S. - Texas - Effects Screening Levels - Long Term                      U.S. - Texas - Effects Screening Levels - Short Term                      U.S. - Vermont - Permissible Exposure Limits - TWAs                      U.S. - Washington - Permissible Exposure Limits - STELs                      U.S. - Washington - Permissible Exposure Limits - TWAs</p>	

### SECTION: 16. Other information

Sources of Key data : Supplier information



# JL-M Lubricant

## Safety Data Sheet

according to ANSI Z400.1

### Abbreviations and acronyms

: ATE - acute toxicity estimate  
BCF - bioconcentration factor  
CAS - Chemical Abstracts Service  
CLP - Classification, Labelling and Packaging  
CSR - Chemical Safety Report  
GHS - Globally Harmonised System  
MSDS - Material Safety Data Sheet  
Overland transport (ADR)  
PBT - Persistent, Bioaccumulative and Toxic substance  
PEL - Permissible Exposure Level  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals  
Relat - Relative  
SDS - Safety Data Sheet  
STEL - Short-Term Exposure Limit  
TLV - Threshold Limit Value  
TWA - Time Weighted Average  
UVCB - Substances of Unknown or Variable composition, Complex reaction products or Biological materials  
vPvB - Very Persistent and Very Bioaccumulative

### Other information

: None.

### NPFA Rating

NPFA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NPFA fire hazard

: 1 - Must be preheated before ignition can occur.

NPFA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health

: 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability

: 1 Slight Hazard

Personal Protection

: B

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*